

ZIP HYDROTAP BC

Order Code HT1784

Zip HydroTap Boiling, Chilled, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	1214AU0H0ZN1R
Capacity	Residential
Disability Options	Available



TapZip HydroTap CLASSIC Tap (Chrome)Water PressureMin 172kPa - Max 700kPaWater Connection12.7mm BSPWater Supply RequirementsColdWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.55kW 220-240V 50 HzPower Supply1 x 10Amp GPODimensionsH333mm x W280mm x D455mmProduct ApprovalsWaterMark, CE, RCM, ARCWarranty5 years (appliance warranty 36 months plus additional 24 months tank warranty)		
Water Connection 12.7mm BSP Water Supply Requirements Cold Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 1.55kW 220-240V 50 Hz Power Supply 1 x 10Amp GPO Dimensions H333mm x W280mm x D455mm Product Approvals WaterMark, CE, RCM, ARC	Тар	Zip HydroTap CLASSIC Tap (Chrome)
Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 1.55kW 220-240V 50 Hz Power Supply 1 x 10Amp GPO Dimensions H333mm x W280mm x D455mm Product Approvals WaterMark, CE, RCM, ARC	Water Pressure	Min 172kPa - Max 700kPa
RequirementsWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating1.55kW 220-240V 50 HzPower Supply1 x 10Amp GPODimensionsH333mm x W280mm x D455mmProduct ApprovalsWaterMark, CE, RCM, ARC	Water Connection	12.7mm BSP
Power Rating 1.55kW 220-240V 50 Hz Power Supply 1 x 10Amp GPO Dimensions H333mm x W280mm x D455mm Product Approvals WaterMark, CE, RCM, ARC		Cold
Power Supply 1 x 10Amp GPO Dimensions H333mm x W280mm x D455mm Product Approvals WaterMark, CE, RCM, ARC	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Dimensions H333mm x W280mm x D455mm Product Approvals WaterMark, CE, RCM, ARC	Power Rating	1.55kW 220-240V 50 Hz
Product Approvals WaterMark, CE, RCM, ARC	Power Supply	1 x 10Amp GPO
	Dimensions	H333mm x W280mm x D455mm
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Product Approvals	WaterMark, CE, RCM, ARC
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

