

## ZIP HYDROTAP G4 4IN1 BCHA 240/175 CUBE MIXER

## Order Code HT1924

Zip HydroTap 4 in 1 Boiling, Chilled, Filtered drinking water plus Hot and Cold washing up water from two seperate taps. The appliance features a single under bench command centre including full colour interactive touch screen display with pin code protection, 2 boiling water safety modes, 3 energy saving modes including sensor activated "sleep when its dark" and 0.2 micron water filtration.

Manufacturing Code	5361AU0H0UN1C
Capacity	Commercial
Disability Options	Unavailable
Boiling Cups per hour	240
Chilled Cups per hour	175



Water Pressure       Min 250kPa - Max 700kPa         Water Connection       12.7mm BSP         Water Supply Requirements       Cold         Water Valves       Integrated 500kPa Pressure limiting valve and Dual Check Valve         Power Rating       2.2kW 220-240V 50/ 60Hz         Booster Power Rating       Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz         Power Supply       2 x 10Amp GPO's (or 1 x 10Amp Double GPO)         Dimensions       H333mm x W394mm x D464mm         Product Approvals       WaterMark, CE, RCM, ARC         Wels Rating       5 Star, 5.5 litres		
Water Connection       12.7mm BSP         Water Supply Requirements       Cold         Water Valves       Integrated 500kPa Pressure limiting valve and Dual Check Valve         Power Rating       2.2kW 220-240V 50/ 60Hz         Booster Power Rating       Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz         Power Supply       2 x 10Amp GPO's (or 1 x 10Amp Double GPO)         Dimensions       H333mm x W394mm x D464mm         Product Approvals       WaterMark, CE, RCM, ARC         Wels Rating       5 Star, 5.5 litres	Тар	Zip HydroTap CLASSIC Tap (Chrome)
Water Supply Requirements  Water Valves  Integrated 500kPa Pressure limiting valve and Dual Check Valve  Power Rating  2.2kW 220-240V 50/ 60Hz  Booster Power Rating  Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz  Power Supply  2 x 10Amp GPO's (or 1 x 10Amp Double GPO)  Dimensions  H333mm x W394mm x D464mm  Product Approvals  WaterMark, CE, RCM, ARC  Wels Rating  5 Star, 5.5 litres	Water Pressure	Min 250kPa - Max 700kPa
RequirementsWater ValvesIntegrated 500kPa Pressure limiting valve and Dual Check ValvePower Rating2.2kW 220-240V 50/ 60HzBooster Power RatingZip HydroTap Booster 2.2kW 220-240V 50/ 60HzPower Supply2 x 10Amp GPO's (or 1 x 10Amp Double GPO)DimensionsH333mm x W394mm x D464mmProduct ApprovalsWaterMark, CE, RCM, ARCWels Rating5 Star, 5.5 litres	Water Connection	12.7mm BSP
Power Rating 2.2kW 220-240V 50/ 60Hz  Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz  Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO)  Dimensions H333mm x W394mm x D464mm  Product Approvals WaterMark, CE, RCM, ARC  Wels Rating 5 Star, 5.5 litres	Water Supply Requirements	Cold
Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz  Power Supply 2 x 10Amp GPO's (or 1 x 10Amp Double GPO)  Dimensions H333mm x W394mm x D464mm  Product Approvals WaterMark, CE, RCM, ARC  Wels Rating 5 Star, 5.5 litres	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Supply       2 x 10Amp GPO's (or 1 x 10Amp Double GPO)         Dimensions       H333mm x W394mm x D464mm         Product Approvals       WaterMark, CE, RCM, ARC         Wels Rating       5 Star, 5.5 litres	Power Rating	2.2kW 220-240V 50/ 60Hz
Dimensions     H333mm x W394mm x D464mm       Product Approvals     WaterMark, CE, RCM, ARC       Wels Rating     5 Star, 5.5 litres	Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/ 60Hz
Product Approvals WaterMark, CE, RCM, ARC  Wels Rating 5 Star, 5.5 litres	Power Supply	2 x 10Amp GPO's (or 1 x 10Amp Double GPO)
Wels Rating 5 Star, 5.5 litres	Dimensions	H333mm x W394mm x D464mm
	Product Approvals	WaterMark, CE, RCM, ARC
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Wels Rating	5 Star, 5.5 litres
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

## Installation Detail

